









SUPERIOR SCRATCH RESISTANCE



PET PROOF



INSTALLATION ON ANY SURFACE



SOUND REDUCING PAD



FAST & SECURE CLIP SYSTEM



100% WATER PROOF





STONE POLYMER COMPOSITE

A Sustainable Flooring Solution

- Eco-Friendly
- Quick and Easy to Install
- Click System
- 100% Waterproof
- Acoustic Qualities
 Sound Reducing Attached Underlay
- Good Foot Feel
- Durable, Easy to Clean / Maintain
- 25-Year Residential Warranty;
 5-Year Commercial Warranty
- Formaldehyde free, Pet friendly
- No scratches, High heel safe no dents



WHY SPC?

Waterproof

100% waterproof, can be installed in kitchens, bathrooms, laundry rooms and restaurants without any worries!

Stability

The SPC vinyl core is more stable in environments with temperature changes, such as cabins, homes with AC units and homes with humidity fluctuations.

Comfort, Healthy & Quiet

Formaldehyde free.

100% natural cork backing makes SPC sturdier, cushioned and softer under foot than a traditional vinyl. No hollow sound when walking on it.

Click-installation system

40% faster to install than glue down floors. It is installed similarly to a regular vinyl and laminate with a click-system installation. No glues or extra tools are required!

Affordability

Budget friendly. No further spending on underlay as it can be installed as-is on the subfloor. Saves time on installation. Makes DIY flooring jobs easier.

Easy Maintenance


Designed to be easily cleaned with regular sweeping and mopping. Same cleaning and maintenance needs as a regular vinyl.

Hardwood Appearance

A variety of looks, textures and styles. SPC can be fitted in bathrooms, kitchens, yoga / fitness studios etc.









SPC COLOUR RANGE





























SPECIFICATIONS

SPC			
PLANK THICKNESS	7MM		
PLANK SIZE	1500MM X 183MM		
вох	8 PCS		
AREA PER BOX	2.20M²		

TECHNICAL DATA			
TYPE	HYBRID		
COLOURS	13		
BACKING LAYER	1.5MM ACOUSTIC CORK		
SUBSTRATE LAYER	ENGINEERED RIGID CORE		
TOP LAYER	DURABLE WEAR LAYER		
PROTECTIVE COATING	CERAMIC MATT UV COATING		
INSTALLATION METHOD	CLICK SYSTEM		



INSPECTION INSTITUTION



TEST REPORT				
TEST ITEM	DATA / CONCLUSION			
WET PENDULUM TEST	SLIP RESISTANCE VALUE: 40	CLASS: P3		
FIRE TEST	MEAN VALUE: 8.6 kW/M ²	CHARRING		
LOCKING STRENGTH	659.2N / 1209N			
ABRASION RESISTANCE	PASS	SWELLING: 0-0.1%		
DBP/ BBP/ DEHP/ DIBP/ DNOP/DMP/ DPhP/ DnHP/ DEP CONTENT(S)	PASS			
PEEL STRENGTH	37.7N/25mm	PASS		
MIGRATIION OF CERTAIN ELEMENTS	PASS			
RESISTANCE TO SURFACE WEAR	PASS			
COLOUR FASTNESS TO LIGHT	BATTER THAN 6 GRADE (B.W.S)			
FORMALDEHYDE	0.003 MG/M ³	EO		
OTHER VOLATILE ORGANIC COMPOUNDS	NOT DETECTABLE	PASS		
ACOUSTIC TEST	L'nT,w: 52 / FIIC: 51	PASS		





